

Date:

Lubrication Survey Form

Pages:

Item	Install Region	Application (equipment) & No.	Bearing No.	RPM	Operating conditions					Active setting	Install date	Lubricator S/No.
					Temperature	Contamination	Moisture	Vibration	Position			
1					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
2					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
3					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
4					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
5					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
6					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
7					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
8					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
9					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
10					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
11					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
12					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
13					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
14					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			
15					1 2 3 4	1 2 3 4	1 2 3 4	1 2 3	1 2 3			

Remark: Indication of a code

- | | | | | |
|---------------------------|--------------------------------------|--------------------------------|----------------------------|--------------------------------|
| Temperature: | 1. below 70°C | 2. 70 to 85°C | 3. 85 to 100°C | 4. above 100°C |
| Contamination: | 1. Light, non-abrasive dust | 2. Heavy, non-abrasive dust | 3. Light, abrasive dust | 4. Heavy, abrasive dust |
| Moisture: | 1. Humidity mostly below 80% | 2. Humidity between 80% to 90% | 3. Occasional condensation | 4. Occasional water on housing |
| Vibration: | 1. Less than 0.2 ips velocity, peak. | 2. 0.2 to 0.4 ips | 3. above 0.4 ips | |
| Shaft orientation: | 1. Horizontal bore centerline | 2. 45 degree bore centerline | 3. Vertical centerline | |